

Connectors - Sherpa Self Tapping Locking Screws






SPECIAL ORDER

Product information

If the connection requires it, the two connecting plates can be held together through the use of specially developed locking screws.

Because these are self tapping screws, there is an optimum ideal fit between aluminium and the thread edges. This ensures high safety against independent loosening, even when exposed to relatively high stresses. Installation of the locking screws requires little effort.

Self Tapping Locking Screws

| | | | |
|-------------------------------------------------------------------------------------|--------------------------------------------------------|------------------------------------------------------------------------------------|----------------------------------------------|
|  | XS Series Dimensions: 3 x 12mm |  | S Series Dimensions: 3 x 20/9mm |
|  | M Series Dimensions: 4 x 20/12mm |  | L Series Dimensions: 5 x 47.8/20mm |
|  | XL & XXL Series Dimensions: 6 x 100/55mm | | |

Fasteners for Concrete Steel Series

| | |
|-----------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------|
| Used for M Series Multi-Monti MMS-F 7.5 x 60 | Used for L, XL & XXL Series Multi-Monti MMS-F 10 x 80 |
| Used for XL Series - Alternative for MMS-F 10 x 80 HL anchor, FH II 12/15 SK Dimensions: 12 x 90mm | |