

## Connectors - Sherpa Special Screws

**SPECIAL ORDER**


### Product information


Screws for SHERPA series XS to XXL. Depending upon the connector type, the relevant special screws must be used as defined in the ETA-12/0067 certification in order to ensure the specified characteristic carrying capability values. These systems screws are yellow zinc galvanised or, if requested, can be obtained with a zinc-nickel layer, and have a strengthened screw head. The head stamping also allows for monitoring even when screwed in.


SHERPA special screws with a rated diameter of 8mm have a patented half tip which reduces the danger of cracking, and provides optimum screw bite.





### Yellow Zinc Galvanised


	<b>X &amp; S Series</b> Dimensions: 4.5 x 50mm
--	---


	<b>Installation Series</b> Dimensions: 5.0 x 60mm
---	--

	<b>M Series</b> Dimensions: 6.5 x 65mm
---	---

	<b>Installation Series</b> Dimensions: 8.0 x 80mm
--	--


	<b>L Series</b> Dimensions: 8.0 x 100mm
---	--


	<b>Installation Series</b> Dimensions: 8.0 x 120mm
--	---


	<b>XL &amp; XXL Series</b> Dimensions: 8.0 x 120mm 8.0 x 140mm 8.0 x 160mm 8.0 x 180mm
---	--

Yellow zinc galvanised for moderate stress - corrosiveness categories C1, C2 and C3 as per EN ISO 12944-2.

### Zinc Nickel

	<b>X &amp; S Series</b> Dimensions: 4.5 x 50mm
---	---

	<b>XL &amp; XXL Series</b> Dimensions: 8.0 x 160mm
--	---

	<b>L Series</b> Dimensions: 8.0 x 100mm
---	--

Zinc-nickel plated, for severe load exposure - corrosive categories C1 to C5 M mong as per EN ISO 12944-2.