



PRODUCT DATA SHEET

OMEGA NDB Nail Sealing Tape ESK

A bitumen tape, adhesive on one side, that is attached along the full length between the diffusive roof underlay and the counter-batten. It prevents ingress of rainwater and guarantees optimum windtightness of the construction. Tested for protection from rain by the Austrian Wood Research Association, (Holzforschung Austria Order no. 203/2003/2 T/HH).

FIELD OF APPLICATION

- a seal for nails and screws below the counter battens

ADVANTAGES

- easy to use
- good adhesion on wood and underlays
- good elastic properties

AVAILABLE IN THE FOLLOWING DIMENSIONS

Type	ESK	ESK	ESK	ESK
Roll width	50 mm	60 mm	70 mm	80 mm
Roll length	10 m	10 m	10 m	10 m
Carton content	20 Rolls	16 Rolls	16 Rolls	12 Rolls

PRODUCT DATA


Material composition	Self-adhesive bitumen tape
Thickness	2 mm
Temperature resistance - Standard	-40 °C - 100 °C
Working temperature	5 °C - 40 °C
Storage	1 year; cool and dry

OMEGA NDB Nail Sealing Tape ESK

Attach OMEGA NDB Nail Sealing Tape ESK to the roof sheeting directly beneath the counter-batten.

The sealing tape encloses the nail completely and achieves a 100 % sealed penetration point! See Guidelines for OMEGA Roof Underlay

The standards according to ÖNORM B 4119 and/or ZVDH (Central Association of German Roofers) must be observed.



ISOCELL GmbH & Co KG

Gewerbestraße 9
5202 NEUMARKT AM WALLERSEE | Österreich
Tel.: +43 6216 4108 | Fax: +43 6216 7979
office@isocell.at

ISOCELL SCHWEIZ AG

Herbergstrasse 29
9524 Zuzwil | Suisse /Schweiz
Tel.: +41 71 940 06 72
office@isocell.ch

ISOCELL FRANCE

170 Rue Jean Monnet | ZAC de Prat Pip Sud
29490 GUIPAVAS | France
Tél.: +33 2 98 42 11 00 | Fax: +33 2 98 42 11 99
contact@isocell-france.fr

ISOCELL BUREEL BELGIË

Außenborner Weg 1 | Schoppen
4770 Amel | Belgique
Tel.: +32 80 39 90 58 | Fax: +32 80 39 97 68
office@isocell.be

ISOCELL Sverige AB

Köpsvängen 10
168 67 BROMMA | Sverige
Tel.: +46 10 130 25 00
info@isocell.se

ISOCELL
www.isocell.com